

DustIQ

for PV soiling monitoring



Know exactly when and where to clean



Optimize yield



The only maintenance free solution to measure soiling



Integrated in the leading monitoring software systems




What if you could measure soiling of PV panels with a solution that does not require any maintenance?! The new DustIQ is a sensor without moving parts, does not need cleaning and uses a breakthrough technology to accurately measure soiling. This fundamental new Optical Soiling Measurement (OSM) technology provides you with insights into the power loss due to soiling. With a network of DustIQs you will know exactly when it is time to clean and where on the plant.





DustIQ for PV soiling monitoring



Dust intensity around world

Benefits of the DustIQ Soiling Monitoring System

- Patented applied for, unique new technology
- Small panel (990 x 160 mm) with solar industry standard materials
- Flexible mounting to fit everywhere: at the side or in the middle of solar arrays
- Measures soiling ratio from 100 % (clean) to 50 %
- Cost effective solution that allows for multiple points of measurement
- Doesn't need sun to operate



Better than alternatives

- Completely passive: no need for daily cleaning as it follows the plant's cleaning schedules
- 24/7 day and night measurements, 1 minute measurement interval
- Multiple sensors are better than existing spot-measurement solutions
- Integration in solar array provides more reliable measurements than existing solutions
- Easy to mount and install

Specifications 0386900 DustIQ Soiling Monitoring System • mounting clips • 10 m cable

Transmission loss (TL) range	0 to 50%
Percentage of sunlight that is blocked or scattered in such a way that it does not reach the actual solar cells	
Soiling Ratio (SR) range	100 to 50 % (SR = 100 -TL)
Transmission loss measurement accuracy	± 0.1 of reading ± 1% (after local dust calibration)
Ambient working temperature	-20 to +60 °C
IP Class	IP65
Communication	Modbus® over 2-wire RS-485
Power	12-30 VDC, 200-70 mA at 24 V, 500 mA power supply is advised
Power consumption	< 2.5 Watt
In rush current	300 mA max.
Glass type	standard PV glass
Dimensions unpacked	990 x 160 x 40 mm (serial number -180093) 990 x 160 x 35 mm (serial number >180093)
Weight packed with 10m cable	6 kg
Weight unpacked	DustIQ unit: 4 kg; Mounting clamps: 600 g; 10 m cable: 400 g